

# SR-2420M

## Slip Roll

24" Length, 20 GA-TTS



Manually powered  
Initial pinch with hardened rolls  
3 wire grooves (.400", .325", .250")  
2" diameter rolls  
165 lbs.

Specifications subject to change without notice.



# SR-3622M

## Slip Roll

36" Length, 22 GA-MS

Manually powered  
Initial pinch with hardened rolls  
3 wire grooves (.447", .380", .285")  
2" diameter rolls  
220 lbs.

Specifications subject to change without notice.



**INITIAL PINCH WITH  
HARDENED  
ROLLS**

# SR-5016M

## Slip Roll

50" Length, 16 GA-17S

**BAILEIGH**  
INDUSTRIAL

Manually powered  
Initial pinch with hardened rolls  
3 wire grooves (.513", .407", .335")  
3" diameter rolls  
Shown with optional floor stand  
462 lbs.

Specifications subject to change without notice.



# SCALED LINEAR BACK ROLL

# SR-5016

Slip Roll  
50" Length, 16 GA-MS



Initial pinch with hardened rolls  
Scaled linear back roll  
3 wire grooves (.513", .407", .335")  
Operator controlled by remote foot pedals  
3" diameter rolls  
Manually adjusted back roll  
220V, single-phase, 60 Hz  
770 lbs.

Specifications subject to change without notice.