



MODEL 150 ROTARY DRAW TUBE & PIPE BENDER

...delivers unmatched versatility, mobility and easy operation!

FEATURES and SPECIFICATIONS

- One shot bending up to 206 degrees without stopping or ratcheting.
- Variable speed controlled by operator.
- Bends pull out in seconds (no disassembly required).
- Unique design coupled with powerful hydraulic pump reduces production time and improves efficiencies.
- Capacity is up to 1-1/2" Schedule 40 Pipe, 1-1/2" square tubing, 1-3/4" Chromolly (up to .083 wall), up to 2.0" tube (.095 wall mild steel).
- Maximum bend radius is 7" (depending on wall thickness, and material).
- Quick release counter die.
- Highly visible degree dial improves accuracy.
- Solid steel construction for durability.
- High quality industrial grade hydraulic system.
- Die sets are interchangeable with all RMD benders.
- High value at reasonable cost.



Above: Heavy-duty construction and extra large degree indicator offers operator reliability and accuracy.

- Bend can be advanced after stopping machine, saves on set up costs (material savings).
- All die sets are color coded for easy identification (green for pipe, blue for tube, and gray for square).
- Power Required: 110 V, Single Phase, 20 amp, 60 cycle (other electrical specifications available).
- Bend Material: Round or square tubing, pipe, flat stock, angle iron, or solid rod.
- Built to the same high quality standards as all other RMD machines.
- **MADE IN AMERICA!**



Above - M-150-S comes standard with cart and industrial grade hydraulics, offering fabricators with limited floor space a powerful, portable piece of equipment. The M-150-S is ideal for: hand railing, marine products, racing chassis and roll cages, fences and gates, furniture frames, hydraulics, and stainless plumbing.



Right - Quick release of product improves production efficiencies.



Left—The M-150-S can produce a 180 degree bend in approximately 23 seconds.



BAILEIGH INDUSTRIAL INC. www.baileighindustrial.com
 Dealer Inquiries Welcome – For further information:
 P.O. Box 531 • Manitowoc, WI 54221-0531 – USA
 Phone: 920.684.4990 • Fax: 920.684.3944